

# PATH-PRO SERIES



## MANEUVERABILITY AND DURABILITY COMBINED.

While lightweight and easy-to-move, Path-Pro® is no pushover. A single-stage that performs like a two-stage, Path-Pro® features a tireless Ariens AX engine, 12.2" housing height and 8.375" paddles capable of clearing up to 9" of snow straight down to the pavement.



### HOUSING & PADDLE

Steel-walled housing shears through snow, while the reinforced rubber paddles and adjustable scraper bar keep things moving.

### FOLDING HANDLEBARS

Folding handlebars make storage a cinch.

### QUICK-ACCESS COVER

With an easy access maintenance hatch, we make it easy to keep your Ariens® running like an Ariens.

### AVAILABLE REMOTE CHUTE

Remote chute rotation gives you the power to let snow fly in any direction you please.

### WHEELS

Enjoy the mobility and agility of Ariens semi-pneumatic wheels.

### AVAILABLE ELECTRIC START

Go ahead. Hit snooze. We promise your Path-Pro will be up and at 'em as soon as you start.

VISIT [ARIENS.COM](http://ARIENS.COM) FOR DETAILS



DESIGNATION	<b>**PATH-PRO 136E</b>	<b>PATH-PRO 208R</b>	<b>PATH-PRO 208E</b>	<b>PATH-PRO 208EC</b>
MODEL #	938034	938031	938032	938033
STAGE TYPE	Single-Stage	Single-Stage	Single-Stage	Single-Stage
ENGINE POWER	136cc (7.0 ft/lbs)	208cc (9.5 ft/lbs)	208cc (9.5 ft/lbs)	208cc (9.5 ft/lbs)
ENGINE BRAND	Ariens AX	Ariens AX	Ariens AX	Ariens AX
STARTING SYSTEM	120V/Recoil	Recoil	120V/Recoil	120V/Recoil
CLEARING WIDTH	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)
HOUSING HEIGHT	12.2 in (31 cm)	12.2 in (31 cm)	12.2 in (31 cm)	12.2 in (31 cm)
THROWING DISTANCE	3ft - 25ft (.9 - 7.62M)	3ft - 35ft (.9 - 10.7M)	3ft - 35ft (.9 - 10.7M)	3ft - 35ft (.9 - 10.7M)
CHUTE TURNING RADIUS	210°	210°	210°	210°
CHUTE ROTATION	Manual	Manual	Manual	Remote
DEFLECTOR CONTROL	Manual	Manual	Manual	Manual
TIRE SIZE	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 1.75 in (19.1 x 4.4 cm)
TIRE TYPE	Semi-Pneumatic	Semi-Pneumatic	Semi-Pneumatic	Semi-Pneumatic
STEERING	Solid Unlocked	Solid Unlocked	Solid Unlocked	Solid Unlocked
DRIVE TYPE	Auger Propelled	Auger Propelled	Auger Propelled	Auger Propelled
SPEEDS	1 Forward	1 Forward	1 Forward	1 Forward
AUGER DIAMETER	8.375 in (21.3 cm)	8.375 in (21.3 cm)	8.375 in (21.3 cm)	8.375 in (21.3 cm)
AUGER TYPE	Reinforced Rubber	Reinforced Rubber	Reinforced Rubber	Reinforced Rubber
SCRAPER BAR	Polymer Adjustable	Polymer Adjustable	Polymer Adjustable	Polymer Adjustable
PRODUCT WARRANTY	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, v 90 day Comm	3yr Cons, 90 day Comm
LENGTH	54.3 in (137.9 cm)	54.3 in (137.9 cm)	54.3 in (137.9 cm)	54.3 in (137.9 cm)
WIDTH	21.6 in (54.9 cm)	21.6 in (54.9 cm)	21.6 in (54.9 cm)	21.6 in (54.9 cm)
HEIGHT	40.9 in (103.9 cm)	40.9 in (103.9 cm)	40.9 in (103.9 cm)	40.9 in (103.9 cm)
WEIGHT	91 lbs (41.3 kg)	91 lbs (41.3 kg)	95 lbs (43.1 kg)	97 lb (43.9 kg)
FEATURES AT A GLANCE	Electric Start, One Hand Interlock	One Hand Interlock	Electric Start, One Hand Interlock	Electric Start, One Hand Interlock